

**METHOD AND ARRANGEMENT FOR COMPUTING AND
REGULATING THE DISTRIBUTION OF A LINEAR LOAD
IN A MULTI-NIP CALENDER AND A MULTI-NIP CALENDER**

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Patent Application Serial No. 09/156,232 filed September 18, 1998 which in turn is a continuation-in-part of U.S. Patent Application Serial No. 09/074,723 filed May 7, 1998, now abandoned, which claims domestic priority of U.S. Provisional Patent Application Serial No. 60/045,871 filed May 7, 1997.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192

lower roll as well as one or more intermediate rolls interposed between the upper roll and the lower roll. The means of suspension of the intermediate rolls are provided with support cylinders, and all the rolls in the set of rolls are preferably supported so that, when the nips are closed, the bending lines of the rolls are curved downwards.

5 Further, the present invention relates to a multi-nip calender for carrying out the method in accordance with the invention.

BACKGROUND OF THE INVENTION

10 In conventional supercalenders or multi-nip calenders, when the nips are closed, the set of rolls is supported from outside the zone of treatment of the web by means of forces which are substantially equal to what is called the pin load applied to the bearing housings of the rolls during running, or which forces are lower than the pin load. The pin load is commonly defined so that it includes the weight of all of the auxiliary equipment connected with the bearing housings of the roll, such as gap shields, doctors, and so-called take-out leading rolls, and also the weight of the portion placed outside the web width and the weight of the bearing system. This prior art has been described best in the paper by Rolf van Haag: "Der Weg zum Load Control-System"; Das Papier, 1990, Heft 7, in which the regulation of the linear load in a conventional supercalender is described. In such supercalenders, the rolls are positioned one above the other so that their middle portions are curved upwards or, in a very rare and special case, are fully straight.

20 The intermediate rolls do not bend in the same way, as compared with one another. Owing to the mode of running, the nip loads in the set of calender rolls are such that the roll masses occurring in the area of the web to be calendered always act with full effect upon all the nip loads placed

underneath the roll concerned. In such a mode of running, it is assumed that the set of rolls is curved in such a way during running that the rigidities of the rolls do not have a substantial effect on the uniformity of the linear loads, and attempts are made to operate the calender based on this assumption so that exclusively the linear loads of the upper roll and of the lower roll are regulated on the basis of measurements of quality.

In Finnish Patent No. 96,334, corresponding to U.S. Pat. No. 5,438,920 (incorporated by reference herein), a calendering method and a calender that applies the method are described, which calender comprises a variable-crown upper roll, a variable-crown lower roll and a number of intermediate rolls placed between the upper roll and the lower roll in nip contact with each other. The rolls are arranged as a substantially vertical stack of rolls on the frame of the calender. A material web to be calendered is passed through the nips formed by the adjacent rolls. The nip load produced by the mass of the rolls in the stack of rolls is eliminated in a specific manner so that all the nips in the calender may be loaded with the desired load, which load is, in a preferred alternative embodiment, equally high in all nips. Thus, the calendering potential could be utilized substantially better than in the earlier calenders. In FI 96,334, it is one of the basic ideas of the prior art calender that rolls bending in the same way are employed in the calender. The conduct of such substantially equally bending rolls in the calender and the simple possibility, permitted by such rolls, of relieving the entire mass of the roll are described, in which case this prior art calender and calendering method differ essentially from the first-mentioned German prior art in the very respect that the effect of the masses of the rolls on the linear loads in the lower nips can be regulated freely.

The prior art described above involves an essential problem. If it is assumed that the

5 natural deflections of the intermediate rolls in the calender without linear loads, i.e., when the nips are open, and the rigidities of the rolls as well as the masses are different, first it is to be stated that such rolls do not comply with those described in FI 96,334 or U.S. Pat. No 5,438,920, in which all of the intermediate rolls had substantially equal deflections. In reality, the manufacture of such rolls, which substantially meet the absolute requirement stated in these publications without separate operations, is very difficult and also expensive, in which connection it has been ascertained that an entirely trivial algorithm of regulation of linear loads, which does not take into account minor differences between the rolls, is not adequate from the point of view of reliable operation of the calender.

OBJECTS AND SUMMARY OF THE INVENTION

10 Accordingly, it is an object of the present invention to provide a solution for the problems related to the prior art calenders by developing a novel mode of thinking, which takes into account the properties of deflection of the rolls.

15 Another object is to provide an improvement over the calender concept described in Finnish Patent No. 96,334 and U.S. Pat. No. 5,438,920, in particular in respect of the manner in which the distribution of linear load can be brought under control in the desired way.

20 In view of achieving these objects and others, in the method in accordance with the invention, in order to compute and regulate the linear loads, one or more of the physical properties affecting the bending of each intermediate roll under load, such as bending rigidity, mass, shape, and material properties, are taken into account, and the ratio of the linear loads applied to the intermediate rolls, the weight of the rolls, and/or the support forces applied to the

rolls are regulated so that the set of rolls is in a state of equilibrium and a predetermined state of deflection. Preferably, all of the above-noted physical properties are determined and taken into account and the ratio of linear loads, weight of the rolls and support forces are all regulated.

5 The arrangement in accordance with the invention includes an automation system and a computing unit arranged to compute and regulate linear loads taking into account the physical properties affecting the bending of each intermediate roll under load, such as bending rigidity, mass, shape, and material properties, and serving to regulate the ratio of the linear loads applied to the intermediate rolls, the weight of the rolls, and the support forces applied to the rolls so that the set of rolls is in a state of equilibrium and in a predetermined state of deflection.

10 The method in accordance with the invention takes into account the properties of rolls of all types, and thus, in some embodiments of the invention, intermediate rolls are employed in the set of rolls in the calender whose bending properties are different from roll to roll.

15 In the computing or computation in accordance with the method and the arrangement of the invention, the set of rolls can be treated as a single unit. On the other hand, the computing can also be carried out individually in respect of each pair of rolls.

The intermediate rolls in the set of rolls are freely moving, so that just forces are applied to the rolls, but the rolls are not held in position.

20 By means of the method and the arrangement in accordance with the invention and by means of the calender intended for carrying out the method, significant advantages are obtained in particular in the respect that, by means of the arrangement in accordance with the invention, the linear loads in each nip can be regulated to the desired level. The arrangement takes into account and computes the deflection lines of the intermediate rolls and the loads of the relief

5 cylinders corresponding to these deflection lines. The rigidities of the intermediate rolls and the differences in the natural deflections of the rolls arising from differences in mass can be readily compensated for in the arrangement by regulating the support forces of the roll support cylinders. Thus, when an arrangement in accordance with the present invention is employed, the deflection lines of all of the intermediate rolls do not have to be identical. The method and the arrangement of the invention can be applied both with a traditional mode of running of a multi-nip calender, in which the paper web runs through all nips, and to a modified mode of running, in which the paper web is passed through certain, desired nips only.

10 Further advantages and characteristic features of the invention will come out better from the following detailed description of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Additional objects of the invention will be apparent from the following description of the preferred embodiment thereof taken in conjunction with the accompanying non-limiting drawings, in which:

FIG. 1 is a general illustration of the arrangement in accordance with the invention which is applied in a multi-nip calender for computing and regulating the distribution of linear load;

20 FIGS. 2A, 2B and 2C are exemplifying illustrations of the regulation of the distribution of linear load in the machine direction that can be achieved by means of the arrangement and method in accordance with the invention;

FIGS. 3A, 3B and 3C illustrate the effects of different calendering parameters on the surface properties of paper;

FIG. 4 is a schematic illustration of the relative arrangement of the data bases included in the automation arrangement in accordance with the invention;

FIG. 5 is a schematic illustration of a four-roll calender that carries into effect the method in accordance with the invention;

5 FIG. 6 is a schematic illustration of an alternative mode of loading in a multi-roll calender in which the set of rolls in the calender is treated by pairs of rolls;

FIGS. 7A, 7B and 7C are schematic side views illustrating alternative embodiments of the set of rolls in a multi-roll calender in which a mode of loading described in relation to FIG. 6 is employed; and

10 FIG. 8 shows a schematic block diagram that illustrates a model of computing in the arrangement in accordance with the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Referring to FIGS. 1-8 wherein like reference numerals refer to the same or similar elements, FIG. 1 is a general view of the arrangement in accordance with the invention in which a calender is denoted generally by reference numeral 10, an automation system is denoted by reference numeral 30, and a computing unit included in the automation system 30 is denoted by reference numeral 40. The calender 10 shown in FIG. 1 has a construction similar to that described, e.g., in Finnish Patent No. 96,334, and thus, the calender 10 comprises a calender
20 frame 11 on which the set of rolls 12 consisting of a number of rolls has been installed substantially in the vertical plane. The set of rolls 12 comprises an upper roll 13, a lower roll 14, and a number of intermediate rolls 15-22 situated between the upper roll 13 and the lower roll 14

one above the other, which rolls are, in the embodiment illustrated in FIG. 1, in nip contact with each other. A paper, board or other material web W is passed over alignment, spreader and take-out leading rolls into the upper nip N_1 and further through the other nips N_2, \dots, N_8 in the calender and finally out through the lower nip N_9 . As shown in FIG. 1, the paper web W is taken, in the
5 gaps between the nips N_1, \dots, N_9 , apart from the faces of the calender rolls by means of take-out leading rolls.

The upper roll 13 in the calender is a variable-crown roll, for example a roll adjustable in zones, having a bearing housing 131 attached directly to the calender frame 11. The axle of the variable-crown upper roll 13 is mounted in the bearing housing 131 and, in a conventional
10 manner, the roll is provided with inside, inner or interior loading means, for example zone cylinders, by whose means the deflection of the roll mantle can be regulated in a desired way.

In a similar manner, the lower roll 14 in the calender is a variable-crown roll, in particular a roll adjustable in zones, having a mantle mounted to rotate about the roll axle and which roll 14 is provided with inner loading means, for example zone cylinders, by whose means the deflection
15 of the roll mantle can be regulated in a desired way. The axle of the lower roll 14 is mounted in bearing housings 141, which have been mounted as shown in FIG. 1, on loading arms 142.

Loading arms 142 are attached to the calender frame 11 pivotally by means of articulated joints 143. Between the calender frame 11 and the loading arms 142, lower cylinders 144 are mounted, by whose means the lower roll 14 can be shifted in the vertical plane. Thus, the set of rolls 12 can
20 be loaded by means of the lower cylinders 144, and further, by means of the lower cylinders 144, if necessary, it is possible to open the set of rolls 12. By means of the zone cylinders of the variable-crown upper and lower rolls 13, 14, in the method and the arrangement in accordance

with the invention, a necessary correction and/or desired regulation of the cross-direction profile of the paper web W can be carried out.

Between the upper and the lower rolls 13,14 in the calender, a number of intermediate rolls 15-22, which are in nip contact with each other, are arranged as stated above. In the following, exclusively the uppermost intermediate roll 15 will be examined, and the related constructions are described in more detail with the aid of reference numerals. A corresponding description can also be applied to the other constructions of intermediate rolls in the calender. The intermediate roll 15 is mounted from its ends to revolve in bearing housings 151. Bearing housings 151 are mounted on lever arms 152, which in turn, are pivotally mounted on the calender frame 11 by means of articulated joints 153 arranged in the axial direction of the roll 15. The lever arms 152 are provided with support means 154, which are preferably hydraulic cylinders. Cylinders 154 are elongate and are attached at one end to the lever arms 152 and at an opposite end to the calender frame 11.

By means of the cylinders 154, a support force is applied to the support constructions of the roll 15 and by means of which force, the loads caused by the weights of the roll 15 and related auxiliary equipment, such as the takeout leading roll 155 (however, always at least the weight of the auxiliary equipment connected with the roll as added with the weight of the parts placed outside the web), can be compensated for and supported in the desired and/or necessary manner. The support can also be carried out so that the loads are supported completely, in which case the weights of the roll 15 and the connected auxiliary equipment have no effect on the nip load, i.e., do not increase the nip load. If such complete support is carried into effect in respect of all of the intermediate rolls 15-22, the linear load in each nip N_1, \dots, N_9 can be made

substantially equally high.

FIG. 2A is a schematic illustration of the situation of loading in the set of rolls, in which connection each nip N_1, \dots, N_9 has an equally high linear load. In this connection, a new term is also introduced in calendering technique, i.e., the loading angle α , because this novel mode of loading cannot be illustrated unequivocally in traditional ways. The loading angle α illustrates the distribution of linear load in the set of rolls from nip to nip, and in the case of FIG. 2A, i.e., in a case of complete relief, the loading angle $\alpha = 90^\circ$. By means of the loading angle α being about 90° , compared with conventional calenders, a significant increase in the calendering potential is obtained. This increase in calendering potential can be utilized in order to increase the running speed of the web through the calender and the productivity of the calender.

The magnitude of the linear load can be regulated fully freely in order to achieve the desired calendering effect, and, in particular in the case of "full relief", i.e., with a loading angle α of about 90° , the calendering effect can be regulated in the way illustrated in FIG. 2A by way of example. A high linear load and a high calendering effect \underline{a} are employed in order to maximize the running speed of the calender, the productivity, and the paper quality. A low linear load and a low calendering effect \underline{a}' are needed under different conditions and in different production stages, such as in matt calendering, in optimizing of quality, in stages of starting up and running down, and in situations of web break. By means of \underline{a} , the solution in accordance with the present invention, a very low calendering effect can be achieved in each nip in the calender, as illustrated in FIG. 2A by way of example.

FIG. 2B illustrates a situation in which, in comparison to a calender with a conventional mode of loading in which the loading angle α is, e.g., about 54° , in a mode of running in

accordance with the present invention, a loading angle $\alpha = 90^\circ$ is employed. As indicated clearly by FIG. 2B, with a mode of running in accordance with the present invention, a significantly lower level of linear load is needed to produce similar properties of quality of paper, i.e., paper having the same properties. However, in accordance with the principles of the invention, it is possible, for example, to minimize the strain applied to the soft-faced rolls in the calender, such as polymer-coated rolls, in particular in the lower part of the set of rolls.

The loads produced by the mass of the intermediate rolls 15-22 in the set of rolls 12 and by the mass of the auxiliary devices connected with these rolls can, if necessary, also be relieved partially, or so that exclusively the pin loads are relieved, in which case, in respect of the distribution of linear load in the set of rolls, for example, a situation as shown in FIG. 2C is reached. As shown in FIG. 2C, the loading angle α can be adjusted, e.g., in a range from about 75° to about 80° . As a result, the linear loads are always increasing in the nips when moving towards a lower nip.

In conventional and traditional supercalenders, the loading angle has generally been in the range of from about 45° to about 55° , and the magnitude of this loading angle has been dependent on the size of the calender, i.e., mainly on the number of rolls. In the method in accordance with the present invention, the magnitude of the loading angle α can be adjusted quite freely, and by means of this adjustability of the loading angle, a considerable advantage and a remarkable improvement are achieved over earlier calendering constructions. The loading angle α can be used as an active variable in fine adjustment of the differences between different faces of the paper. Adjustment of two-sidedness has a significant effect on the properties of quality of paper, and in this manner, by means of the present invention, it is possible to produce paper of

uniform quality reel after reel. A corresponding property has not been suggested anywhere else previously.

The support can, of course, also be accomplished, for example, as a what is called "excessive relief", wherein the loading angle α is larger than 90° . In such a case, it is possible to reach a situation in which a lower nip always has a lower linear load than the nip placed above has. Such an embodiment has, however, not been illustrated herein.

In order to establish the significance of the loading angle α and its adjustability in comparison with other calendering parameters or variables, an extensive test program has been carried out with a test machine, and an example of the test results is given in FIGS. 3A, 3B and 3C, which illustrate the effects of different calendering parameters with different paper grades. In FIG. 3A, the paper grade is SC paper, in FIG. 3B, the grade is LWC paper, and in FIG. 3C, the grade is WFC paper. The effects of different factors on the surface properties of paper (gloss, roughness/smoothness) were determined by means of the results, which were obtained by changing the calendering parameters to a certain extent. The variables that were used were running speed, linear load, temperature, and loading angle, as follows:

Speed: change in speed about 200 meters per minute

Linear load: change in load about 50 kN/m

Temperature: change in surface temperature of heated roll about 15°C

Loading angle: change in loading angle from about 50° to about 90° (50° represents the loading with a traditional mode of supercalendering, and 90° represents an angle which can be obtained with the

method in accordance with the present invention)

As seen clearly from FIGS. 3A, 3B and 3C, the effect of a change in loading angle on improvement of the surface properties of paper is higher than with any other calendering parameter.

FIG. 1, and also FIGS. 2A, 2B and 2C, illustrate an embodiment in which the set of rolls 12 consisting of the rolls has been installed substantially vertically. The solution is, of course, not confined to such an embodiment only, but the set of rolls can be placed in an obliquely vertical position at least to some extent diverging from the straight, vertical position. Of the rolls included in the set of rolls 12, one or several may be soft-coated polymer rolls and/or paper rolls, fiber rolls or other soft-faced rolls. In the exemplifying embodiment shown in FIG. 1, the upper and lower rolls 13,14 are provided with a soft polymer coating, the first, third, sixth, and eighth intermediate rolls 15,17,20, and 22 are hard-faced chilled rolls, and the second, fourth, fifth, and seventh intermediate rolls 16,18,19,21 are soft-coated polymer rolls. The number of the intermediate rolls or the relative sequence and arrangement of the soft-faced/hard rolls is, however, in no way confined to the exemplifying embodiment of FIG. 1.

In the method in accordance with the present invention, a situation corresponding to a normal production situation is examined, in which case the set of rolls 12 is closed in the way shown in FIG. 1 and the rolls 13-22 are under load in contact with one another. As shown in FIG. 1, the automation system 30 included in the arrangement in accordance with the invention is connected to the support cylinders 154 to measure and control the loads of the relief cylinders. In the method to be examined, in the nips N_1, \dots, N_9 , in the set of rolls 12, in the running direction of

the paper web W, a uniform or different, desired distribution of linear load is formed so that in the automation system 30 the deflection lines of the intermediate rolls 15-22 and the corresponding loads of the cylinders 154 of support of the intermediate rolls are computed. The support cylinders 154 and the lever arms 152 are used for supporting the mass of the intermediate rolls 15-22 and the masses of the auxiliary devices connected with the intermediate rolls.

As was already stated with reference to FIGS. 2A, 2B and 2C, the distribution of linear load in the machine direction is regulated by supporting the mass of the rolls and the connected auxiliary devices completely. Thus, besides the mass of the intermediate rolls, by means of the support cylinders 154 and the lever arms 152, the mass of the auxiliary devices connected with the lever arms of each intermediate roll, such as take-out leading rolls, possible doctors, etc., are also supported. The rigidities and mass of the intermediate rolls 15-22 are not equal from roll to roll. Correction of the errors in the cross-direction profiles of the deflection lines of the rolls, arising from these differences in rigidity and mass, i.e., regulation of the deflection lines of the intermediate rolls, is carried out by correcting the loads of the support cylinders of the intermediate rolls from their nominal value by means of the necessary term corresponding to the difference in pressure. The regulation of the deflection lines of the variable-crown upper roll and lower roll 13, 14 is carried out in a conventional manner by means of the zone cylinders in the rolls. When the deflection lines of the variable-crown upper and lower roll 13, 14 are regulated so that they are equal to the deflection lines of the intermediate rolls 15-22, it is possible to give the set of rolls 12 the desired level of linear load in the machine direction by hydraulically loading either the upper roll or the lower roll. In the case of FIG. 1, this loading can be arranged by means of the lower roll 14, because the loading cylinders 144 have been connected to act upon

the lower roll.

In the method and the arrangement in accordance with the invention, the necessary correction and regulation of the cross-direction profile of paper, e.g., of thickness and/or glaze, is carried out by means of the zone cylinders in the variable-crown upper and lower roll 13,14. In the intermediate nips, i.e., in the nips N_2, \dots, N_8 between the intermediate rolls 15-22, correction of the cross-direction profile can be carried out by means of regulation of the loading of the relief cylinders of the intermediate rolls. The method in accordance with the invention and the related computing of the distribution of the linear load in the set of rolls 12 can be applied both to a traditional mode of running of a multi-nip calender, wherein the paper web W runs through all of the nips N_1, \dots, N_9 , and to a modified mode of running, wherein the paper web W is passed through certain nips only. In the method in accordance with the invention, the automation system includes programs for maintenance of the set of rolls, distributions of linear load, roll parameters, and recipe data bases which, together with the program for computing the distribution of linear load, permit computing of the distributions of linear load specifically for each paper grade. Further, for maintaining the changes in the set of rolls in the calender and for monitoring the stock of rolls, there are program routines of their own.

The distribution of linear load in the set of rolls 12 and the support forces to be passed to the support cylinders of the intermediate rolls 15-22 are computed either in the automation system 30 or in a separate computing unit directly connected with the automation system. The computing model determines the rigidity and the mass distribution of the set of rolls 12 in the calender 10 consisting of chilled rolls and polymer rolls as well as the rigidity of the nips N_1, \dots, N_9 between the rolls. Further, in the computing, the locations and masses of the outside masses

connected with the set of rolls are determined, the effect of temperature on the modulus of elasticity is taken into account, the effect of the roll diameters on the original modulus of elasticity is taken into account, a possible additional linear load of the rolls and the separate effects of the centers of mass and gravity of the roll ends at the tending side and at the driving side are taken into account. The data employed in computing are divided into general calender-specific, nip-specific, and roll-specific data. Thus, the starting-value data necessary for the computing are defined in a roll data base 51, in a roll material data base 52, in a set-of-rolls mass data base 53, in a data base of geometry of the articulated linkage in the calender, i.e., in the set-of-rolls data base 54, as illustrated schematically in FIG. 4. In the computing model applied in the invention, the computing is preferably carried out in two stages so that in the first stage, the support pressures of the intermediate rolls are optimized and correction coefficients are obtained for the variable-crown upper and lower rolls. This data is utilized in the second stage of computing for optimizing the distribution of linear load of the upper roll and the lower roll.

The way in which the calender in accordance with the invention can be made to operate in the desired way, i.e., in which the forces that support the intermediate rolls are determined, is derived from the procedure in accordance with the invention, by whose means the ratio of the linear loads applied to the intermediate rolls, the weight of such rolls, and the support forces applied to such rolls is adjusted to such a level that a pre-determined state of deflection prevails in the area of the set of rolls. In the determination of the deflection of each roll, it is also possible to include a possible mode of grinding of the roll concerned, or the roll in nip contact with the same, to a shape different from the traditional cylindrical shape, such as a positive or negative crown.

When the basic load and the correction of linear load produced by means of the variable-crown rolls operating as end rolls are taken into account in the solution of the equations of deflection of the intermediate rolls, in every case it is possible to achieve such a state of equilibrium for the set of rolls that the distributions of linear load in the nips in the set of rolls correspond to the desired distribution of linear load.

The group of equations that has been formed and that illustrates the conduct of the set of rolls can be solved convergently by means of commonly used numeric solution algorithms of groups of equations. An example of this is FIG. 5, which illustrates a four-roll supercalender, in which the set of rolls 100 comprises a variable-crown lower roll 111, a variable-crown upper roll 112, and two intermediate rolls 113, 114. The nip load in the nips N_{101} , N_{102} , N_{103} between the rolls is produced substantially as the spring force required to produce an elastic compression of the coating on one of the rolls that form a nip. Since, at each point, the force is proportional to the difference between the transitions arising in the rolls at the nip, it can be concluded directly that at each point the same load is achieved when the difference in transition at the points is the same, i.e., when the deflection lines of the rolls are of equal shape and equal magnitude. Thus, the optimal relief or support of each roll is determined so that the bending load that remains on each roll mantle produces an equally high deflection on all rolls.

Since normally, the deflection forms of rolls are equal (paraboloidal), in the examination referring to FIG. 5 the deflection of the roll will be described exclusively by means of the deflection of the center point of the roll.

The deflection of a roll as a result of a deflecting linear load produced on the roll mantle can be expressed by means of the formula:

$$\delta_t = k \cdot (q_{ts} / (E_t \cdot l_t))$$

from which the load is obtained by means of the deflection:

$$q_{ts} = ((E_t \cdot l_t) / k) \cdot \delta_t$$

5 wherein:

δ_t = deflection of roll;

k = coefficient depending on mode of loading;

q_{ts} = linear load that deflects the roll;

E_t = modulus of elasticity of roll;

l_t = inertia of roll.

The sum of the loads that deflect the intermediate rolls in the whole set of rolls:

$$\Delta Q = \Sigma q_{ts} = \Sigma (((E_t \cdot l_t) / k) \cdot \delta_t)$$

wherein

ΔQ = change in overall load in the area of the set of rolls

The load that deflects the roll mantle expressed by means of component loads:

$$q_{ts} = G_{tv} / L + q_{ty} - q_{ta} + q_{ti}$$

wherein:

G_{tv} = weight of roll mantle;

q_{ty} = linear load in upper nip of roll;

q_{ta} = linear load in lower nip of roll;

q_{ti} = additional linear load arising from other factors in the area of the

roll mantle.

When it is taken into account that, in an intermediate nip between rolls, the upper and lower nip loads of adjacent rolls are of equal magnitude, the sum of the loads that deflect the intermediate rolls in the whole set of rolls is obtained as:

$$\Delta Q = \Sigma q_{ts} = \Sigma (G_{iv}/L) + q_{yy} - q_{aa} + \Sigma q_{ti}$$

wherein

$$q_{yy} = \text{linear load in the upper nip of the set of rolls}$$

$$q_{aa} = \text{linear load in the lower nip of the set of rolls}$$

When the deflections of the rolls are denoted equal and when they are substituted further, what is obtained is:

$$\delta = \delta_t$$

$$\Rightarrow \Delta Q = \delta/k \cdot \Sigma (E_t \cdot l_t)$$

$$\delta = \delta_t = \delta_o = (\Delta Q \cdot k) / \Sigma (E_t \cdot l_t)$$

When this is substituted further in the formula of the load that deflects a roll, what is obtained is:

$$q_{ts} = (E_t \cdot l_t) / \Sigma (E_t \cdot l_t) \cdot \Delta Q$$

Regarding the equilibrium of forces in a roll, the required support force per side is solved:

$$F_{tk} = 1/2 \cdot q_{ts} \cdot L + G_{tp}$$

$$\Rightarrow F_{tk} = 1/2 \cdot (E_t \cdot l_t) / \Sigma (E_t \cdot l_t) \cdot \Delta Q \cdot L + G_{tp}$$

wherein:

$$F_{tk} = \text{support force of roll per side;}$$

L = nip length;

G_{tp} = weight of end parts of roll per side.

The computing of the support forces of the set of rolls in the calender, expressly of the entire set of rolls, is based on knowledge of the exact physical properties of the rolls, i.e., the conduct of all the rolls is known when deflecting loads of different magnitudes are applied to the rolls. It is a basis of the computing that the bearing support forces applied to each roll are determined so that the entire set of roll obtains an equally high calculatory deflection. Thus, by means of regulation of the support forces, it is possible to affect the ratio of the upper nip load and the lower nip load at an individual roll so that the sum of these loads, together with the respective mass of the roll, produces the same predetermined deflection in each individual roll.

The computing can be applied to a set of rolls of any kind whatsoever in a calender, which set of rolls is placed in a substantially vertical position, in which set of rolls the upper roll is an adjustable-crown roll and the lower roll likewise an adjustable-crown roll, the axial distribution of support forces of the upper and lower roll being adjustable, and in which set of rolls there are at least two intermediate rolls between the upper roll and the lower roll. Further, it is an important requirement that all the rolls in the set of rolls are supported so that their deflection lines are downwards curved when the nips are closed.

It is an important characteristic feature of the method, the arrangement, and the calender in accordance with the invention that, when computing the linear loads in the set of rolls, the physical properties of each intermediate roll that affect the deflection under load, such as bending rigidity, mass, shape, and material properties, are taken into account.

It is a further property that the bearing support forces of the intermediate rolls are

determined by means of computing so that the overall load applied to each intermediate roll subjects each intermediate roll substantially to a calculatory deflection such that the deflection forms of the contact faces of each roll, and the roll(s) in contact therewith in a nip, substantially correspond to one another.

5 The nip forces in a calender are regulated so that the difference between the nip forces of the uppermost nip and the lowest nip in the calender is determined to be at the desired level. This means, in fact, the regulation of the loading angle α that was described in relation to FIGS. 2A, 2B and 2C.

10 To briefly summarize the foregoing, it can be stated further that it is an important feature of the invention that all the intermediate rolls in the set of rolls are supported to a greater extent than what is required by the pin forces (all mass outside the web). In such a case, the deflection lines of the rolls are downwards curved and substantially paraboloidal (parabolic). The support forces of each intermediate roll are regulated so that the deflection of the roll is adapted to the shapes of the other rolls in the set of rolls. Thus, the computing is carried out by means of the
15 deflections. In this way, a group of equations is obtained in which the basic load between the rolls is determined so that the deflections of all the rolls are substantially equal. Thus, an equilibrium of forces is produced in the set of rolls. As the loading angle α , it is possible to use any loading angle whatsoever, and the regulation of the loading angle α is carried out by means of outside loading members through the lower roll and the upper roll. As a result, in the
20 regulation of the deflection, the variable is the support force with which the roll is supported. Any errors produced by the mass of the areas outside the web in the distribution of linear load (and possibly other errors in the distribution of linear load) are corrected by means of the

adjustable-crown upper and lower rolls.

As shown in FIG. 6, the invention provides a novel possibility of taking care of the loading and the regulation of loading in the set of rolls in a multi-roll calender by the pair of rolls, which makes the system of regulation simpler and easier to carry into effect. As described above, in conventional supercalenders, generally rolls of two different types are employed as intermediate rolls and the rigidities of these two roll types are different. More particularly, as the intermediate rolls, hard-faced heatable rolls are used, on one hand, and soft-faced rolls are used, on the other hand, which soft-faced rolls can be conventional paper rolls or fiber rolls, which have been formed by fitting disks made of paper or of some other fibrous material onto the roll axle. As soft-faced rolls, today, ever increasing use is made of polymer-faced rolls, in which the roll frame consists of a tubular roll mantle. The rigidities of rolls of the same roll type are substantially equal to one another, but as stated above, the roll types differ from one another essentially with respect to rigidity and thus, also with respect to the deflection arising from the own mass.

In a conventional supercalender, the set of rolls comprises a stack of rolls placed in a substantially vertical or obliquely vertical position, wherein the rolls rest one on the other and the pin loads applied to the bearing housings of the rolls have been relieved hydraulically. The loading and profiling of the set of rolls is taken care of by means of variable-crown upper and lower rolls.

In the alternative mode of loading shown in FIG. 6, the set of rolls is treated as pairs of rolls 200, which consist of a more rigid roll 202 placed as the lower half in the pair of rolls 200 and a more flexible roll 201 placed as the upper half. Any deflection arising from the mass of the

upper roll 201 per se is higher than the deflection of the lower roll 202 in the pair. The pairs of rolls 200 in the set of rolls are substantially similar to one another, and they have equal, common deflections depending on the mass and rigidities of the rolls 201,202.

A force F_2 is applied to the bearing housings of the upper and more flexible roll 201 in the pair of rolls 200, for example a hydraulic force, and by whose means, besides relief of the pin loads, any error in the distribution of linear load between the rolls may be compensated for. Such errors might arise from the different rigidities of the rolls 201,202. This can be illustrated by means of the formula:

$$2F_2 = m_{add2},$$

wherein:

$$F_2 = \text{force applied to the bearing housings of upper roll;}$$

$$m_{add2} = \text{mass of the bearing housings and the auxiliary devices attached to the bearing housing as well as the above error arising from different rigidities of the rolls.}$$

Thus, the upper roll 201 rests with its own weight m_2 (from which the pin loads have been "cleaned") on the lower roll 202 and applies an even linear load m_2/L to the lower roll, wherein L is the axial length of the nip N between the rolls 201,202. On the other hand, a force F_1 is applied to the bearing housings of the lower roll 202 in the pair of rolls 200, by means of which force the mass of both rolls 101,102 in the pair of rolls 200 as well as the pin loads of the lower roll 202 are supported. This can be illustrated by means of the formula:

$$2F_1 = m_1 + m_2 + m_{add1},$$

wherein:

F_1 = force applied to the bearing housings of the lower roll;
 m_1 = mass of lower roll;
 m_2 = mass of upper roll;
 m_{add1} = mass of the bearing housings of the lower roll and the auxiliary
 5 devices attached to the bearing housings.

Thus, in an optimal situation, between the separate pairs of rolls 200, no forces arising
 from the mass of the rolls are effective at all. In the nip N between the rolls 201,202 of the pair
 of rolls 200, exclusively the linear load arising from the mass of the upper roll 201 is effective,
 for example about from about 10 to about 20 kN/m. Owing to the differences between individual
 10 rolls, the whole set of rolls must be treated as a whole, and the reliefs of each roll must be
 optimized so that the cross-direction profile of linear load of the whole unit is as straight as
 possible and the linear load arising from the mass of the rolls is as low as possible. In this
 manner, a set of rolls with almost uniform loading is obtained, which set of rolls is, in most other
 respects, loaded in the manner described above. For example, when a load of about 300 kN/m is
 15 considered as the load level, in every second nip there is a difference in loading of about 5 per
 cent only, as compared with the preceding or the following nip, i.e., with existing rolls, a
 substantially even distribution of load is achieved.

Above, in connection with the description related to FIG. 6, for the sake of simplicity, it
 has been assumed that the rigidities of the rolls 201,202 in the pair of rolls 200 are at a certain
 20 ratio to one another and that the rigidities of the rolls belonging to the same type of rolls are
 substantially equal to one another. However, as established above in relation to FIG. 5 clearly by
 means of computing, there would not seem to exist any limitation arising from the mutual ratios

of the extents of specific deflections of the rolls. Thus any ratio of the rigidities of two rolls whatsoever can be compensated by means of computing so that the magnitudes of the linear loads in the whole set of rolls can be regulated so that they become substantially equal, with the exception of the deviation caused by the internal nips in calculatory pairs of rolls.

5 When conventional upper and lower rolls, for example rolls adjustable in zones, are used, a factor that limits uniform loading is the overall deflection of the intermediate rolls. This limitation could, however, be compensated for so that, if necessary, the lower roll is ground so that its diameter is smaller at the middle than at the ends (negative crown), so that the attainable maximal deflection of the roll adjustable in zones, together with the grinding shape, achieves the maximal possible deflection of the set of rolls. In this connection, it should be noted that, in a set of rolls of this type, the general direction of deflection of the rolls differs in such a way from the direction of deflection of so-called conventional supercalenders that the rolls are in a downwards curved position, instead of the upward curve form employed in a conventional supercalender.

10 In the regulation of loading carried out by the pair of rolls, in the set of rolls in a supercalender, compared with the illustration of FIG. 6, a difference is caused by the reversing nip in the calender, i.e., the nip in which the side of calendering of the web is changed.

15 Generally, this reversing nip is the middle nip in the supercalender. This is illustrated in FIGS. 7A, 7B and 7C, in which three alternative modes of loading in a reversing nip are shown. In these figures, the pairs of rolls as shown in FIG. 6 and identical with one another are denoted by reference numeral 200. In a supercalender, the reversing nip is a nip that is formed between two
20 soft-faced rolls 201, and in FIGS. 7A, 7B and 7C this reversing nip is denoted by N_e .

 In the embodiment shown in FIG. 7A, this has been accomplished so that, in the "pair" of

rolls 200_e, which is in this case formed by three rolls placed one above the other, the lower roll 202, which is a hard-faced and, for example, heatable roll, has a higher rigidity than the lower rolls in the other pairs of rolls 200. This is because the mass of the two upper rolls 201 rest on the lower roll 202.

5 In FIG. 7B, a corresponding construction has been accomplished so that the upper soft-faced roll 201_{e1} in the reversing nip N_e is arranged as a variable-crown roll. In such a construction, the deflection of the roll 201_{e1} is corrected by means of the crown variation means situated in the interior of the roll, and the mass of the roll does not load the pair of rolls 200_{e1} placed underneath by means of its weight.

10 In FIG. 7C, a corresponding construction has been accomplished so that the upper soft-faced roll 201_{e2} in the reversing nip N_e has been arranged as a roll with such a rigidity that its deflection is the same as the deflection of the whole pair of rolls 200,200_{e2}. In such a case, the roll in the reversing nip does not cause any problem in the regulation of the loading.

15 With reference to FIG. 8, in the computing, in accordance with the invention, first the initial values of the rolls are defined, and a mathematical model corresponding to the set of rolls is formed on this basis. The mathematical model is formed in compliance with the number of rolls included in the set of rolls. The optimization computing formed for the set of rolls uses these data as the starting data. In the optimization computing that is to be carried out, the nip errors of the intermediate rolls are minimized, which errors have been defined as deviations from
20 the nominal form. The resilience occurring between each nip and arising from the paper and from the coatings is illustrated by a base constant, which is computed across the nip length. The effects of the forces to be optimized on the linear load are determined in a response data base, in

which the unit response of the element of the nip of each intermediate roll is indicated in a desired number of examination points. The effects of invariable forces on the linear load are determined in a separate invariable-force data base, which takes into account divided masses, point masses, and nips with invariable load. Further, for the computing, the effects of the forces
5 to be optimized on the restrictions and the effects of backup forces on the tension restrictions are determined. Thus, the optimization becomes a mathematical problem, in which the variables are limited and determined by groups of equations. As a result of the computing, optimal relief forces for intermediate rolls, optimal profiles of linear load and deflections of rolls are obtained.

After the computing operation, the optimized support forces of the intermediate rolls in the set of rolls of the calender are transferred to the support cylinders of intermediate rolls, as illustrated, for example, in FIG. 1. The optimized support forces of intermediate rolls are also transferred to the program of computing of the zone pressures of the variable-crown upper and lower rolls. The deflection values of the intermediate rolls in the set of rolls are used for controlling and regulating the variable-crown upper and lower rolls. From the deflection values of the intermediate rolls, by means of a separate computing program, the zone pressure corrections of the upper and the lower roll are determined, which corrections are, in each particular case, added to, or reduced from, each actual value of zone pressure. The distribution of linear load in the set of rolls is controlled in the method in accordance with the invention so that, by means of the user interface of the automation system, first the desired form of the
20 distribution of linear load is determined. After this, the automation system and the included computing programs compute the above set values for the support pressures of the intermediate rolls and the zone pressures of the variable-crown upper and lower rolls. The method in

accordance with the invention also takes into account situations of change in the set of rolls arising from change of roll or from a new mode of running as well as any changes arising from such situations of change in the set-of-rolls data base, the parameter data bases and the computing. Likewise, in its roll and material data bases, the method covers and takes into account situations in which the diameters and/or material properties of chilled rolls and/or polymer rolls are changed.

With regard to the process conditions of calendering, it can be stated generally that they are determined by the capacities of the components that are used as rolls, as is also ordinary in calender technology. Further, restrictive factors in the process include the desired properties of paper, such as bulk (stiffness), smoothness/roughness, and gloss, in particular gloss of printing paper. As examples of process conditions, reference is made to U.S. Pat. Nos. 4,749,445 and 4,624,744 by S.D. Warren. A possible range of surface temperature of a heatable, so-called thermo roll is $T_s =$ about 60°C to about 250 °C, depending on the running speed so that the surface temperature is lower at low running speeds and higher at high running speeds. This is because the time of effect of the nip is shorter and thus, the transfer of heat from the thermo roll to the web face is lower. The range of variation of linear load can be from about 20 kN/m to about 550 kN/m or even higher, again depending on the running speed and the properties of the variable-crown upper and lower rolls that produce the linear load in the supercalender.

Above, some preferred embodiments of the invention have been described, and it is obvious to a person skilled in the art that numerous modifications can be made to these embodiments within the scope of the inventive idea defined in the accompanying patent claims. As such, the examples provided above are not meant to be exclusive. Many other variations of

the present invention would be obvious to those skilled in the art, and are contemplated to be within the scope of the appended claims.

66E050" 265E0160